



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : G06T 11/00	A1	(11) International Publication Number: WO 96/39683 (43) International Publication Date: 12 December 1996 (12.12.96)
(21) International Application Number: PCT/US96/07301 (22) International Filing Date: 20 May 1996 (20.05.96) (30) Priority Data: 08/473,653 6 June 1995 (06.06.95) US (71) Applicant: APPLE COMPUTER, INC. [US/US]; 1 Infinite Loop - MS: 38-PAT, Cupertino, CA 95014 (US). (72) Inventors: ANDRESEN, Kevin, W.; 66 Shelley Avenue, Campbell, CA 95008 (US). CHAN, Allen, M.; 880 E. Fremont Avenue #628, Sunnyvale, CA 94087 (US). FISHMAN, Robert, C.; 810 Piper Avenue, Sunnyvale, CA 94087 (US). WALKER, Ted, W.; 857 W. Remington Drive, Sunnyvale, CA 94087 (US). (74) Agents: CARMICHAEL, Paul, D. et al.; Apple Computer, Inc., 1 Infinite Loop - MS: 38-PAT, Cupertino, CA 95014 (US).		(81) Designated States: AL, AM, AT, AU, AZ, BB, BG, BR, BY, CA, CH, CN, CZ, DE, DK, EE, ES, FI, GB, GE, HU, IS, JP, KE, KG, KP, KR, KZ, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, TJ, TM, TR, TT, UA, UG, UZ, VN, ARIPO patent (KE, LS, MW, SD, SZ, UG), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG). Published <i>With international search report.</i>
(54) Title: METHOD AND SYSTEM FOR RENDERING BI-LEVEL IMAGE DATA FOR IMAGE OUTPUT DEVICES (57) Abstract <p>An image to be generated is analyzed to determine whether it is comprised solely of bi-level color data. If so, an indication is provided to a rendering device that a simpler rendering procedure, suitable for bi-level data, can be employed. However, full color information pertaining to the image is retained. If the rendering device is able to process the image data in a bi-level format, it does so, to thereby improve performance and reduce the amount of memory capacity that is required. If multi-level data is detected, the bi-level data is expanded and full color rendering is carried out in a conventional fashion.</p>		

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AM	Armenia	GB	United Kingdom	MW	Malawi
AT	Austria	GE	Georgia	MX	Mexico
AU	Australia	GN	Guinea	NE	Niger
BB	Barbados	GR	Greece	NL	Netherlands
BE	Belgium	HU	Hungary	NO	Norway
BF	Burkina Faso	IE	Ireland	NZ	New Zealand
BG	Bulgaria	IT	Italy	PL	Poland
BJ	Benin	JP	Japan	PT	Portugal
BR	Brazil	KE	Kenya	RO	Romania
BY	Belarus	KG	Kyrgyzstan	RU	Russian Federation
CA	Canada	KP	Democratic People's Republic of Korea	SD	Sudan
CF	Central African Republic	KR	Republic of Korea	SE	Sweden
CG	Congo	KZ	Kazakhstan	SG	Singapore
CH	Switzerland	LI	Liechtenstein	SI	Slovenia
CI	Côte d'Ivoire	LK	Sri Lanka	SK	Slovakia
CM	Cameroon	LR	Liberia	SN	Senegal
CN	China	LT	Lithuania	SZ	Swaziland
CS	Czechoslovakia	LU	Luxembourg	TD	Chad
CZ	Czech Republic	LV	Latvia	TG	Togo
DE	Germany	MC	Monaco	TJ	Tajikistan
DK	Denmark	MD	Republic of Moldova	TT	Trinidad and Tobago
EE	Estonia	MG	Madagascar	UA	Ukraine
ES	Spain	ML	Mali	UG	Uganda
FI	Finland	MN	Mongolia	US	United States of America
FR	France	MR	Mauritania	UZ	Uzbekistan
GA	Gabon			VN	Viet Nam

METHOD AND SYSTEM FOR RENDERING BI-LEVEL IMAGE DATA FOR IMAGE OUTPUT DEVICES

Technical Field

- 5 The present invention is directed to imaging systems, and more particularly to the manner in which bi-level data is processed to produce an image on output devices in such systems.

Background

- 10 Output devices for imaging systems, such as display monitors and printers, operate as raster devices, whose output images comprise a two-dimensional grid of picture elements, or pixels, that is known as a "raster." To generate an image on a screen or a page, these devices store a representation in memory of a display value for each pixel in the image. This stored
15 representation of the image is referred to as a "pixel map" (sometimes abbreviated as "pixmap"), or a frame buffer. The stored value for each pixel represents the amount of each color component that is present in the image at a sample point corresponding to the location of the pixel. For example, a color monitor represents colors in terms of their red, green and blue components.
20 Therefore, the frame buffer for a color monitor stores values which indicate how much red, green and blue is to be displayed in the image at the point corresponding to the pixel. Conversely, a color printer may represent colors in terms of cyan, magenta and yellow components. Consequently, its frame buffer stores pixel values that represent the amount of cyan, magenta and
25 yellow to be printed in each pixel. A monochrome display device or printer may have the capability to represent different intensity levels of one color, e.g. different grayscale levels. In such a case, the frame buffer stores values relating to the intensity levels. In this regard, it is to be noted that the term "color", as used in the context of the present invention, can refer to grayscale levels as
30 well as chromatic values.

- In the operation of an exemplary imaging system, a user might be running a graphics application program on a computer. The user can instruct the program to draw an object, such as a square, at a particular location on the screen of the display monitor. In response to the user inputs, the graphics
35 program issues high level instructions to the computer's operating system to draw the objects. A display manager, or similar such portion of the computer's operating system for controlling the operation of the display monitor, interprets the commands into low-level instructions for the monitor. As part

of this interpretation process, the high-level description of the object from the application program is translated into individual pixel display values that are stored in the frame buffer. This process of converting the high-level graphical data into pixel values is known as rendering. A similar type of operation
5 occurs when the image is to be printed on a printer. In this case, the frame buffer which stores the pixel values is sometimes known as a page buffer.

Each pixel of an image describes a uniquely addressable area of the output device which can reproduce one or more display or print values. If a device can represent more than one intermediate value of gray, it is called a
10 grayscale device. The number of levels is usually a power of two which enables pixel values to be binary encoded. For example, a pixel which can represent 4 levels of gray can be encoded in a 2-bit binary number, where each binary value indexes one of the levels of gray. The number of bits that represent the display value in a pixel is often called pixel depth. Color devices
15 with a pixel depth of 8 bits per component are often called true color, continuous tone, or contone devices. The term "continuous tone" is actually a misnomer when used in connection with these devices, since the pixels are quantized to discrete digital values. Therefore, the term "multilevel" is used to describe all devices with a pixel depth greater than one, whether color or
20 grayscale.

A device which represents colors with one bit per pixel is known as a bilevel device. Basically, the state of the bit can indicate whether a pixel is "on", e.g. a black dot is printed, or "off", where nothing is printed and the pixel takes on the color of the background medium, such as a sheet of paper.
25 Alternatively, the state of the pixel might indicate two different colors that are to be printed or displayed.

Bi-level devices represent intermediate levels via techniques such as halftoning or dithering, which attempt to reproduce a desired level, or intensity, over an area of several pixels. Multilevel devices can represent
30 intermediate levels directly within a single pixel. Therefore, 50% gray reproduced on a monochrome bi-level device looks different than 50% gray reproduced on a multilevel device. However, black and white look the same on both devices -- each pixel is either entirely on, e.g., black, or entirely off, to represent white.

35 The rendering process requires an appreciable amount of processing power, and hence time, in the overall generation of a image. For a high resolution image, the frame buffer also requires a significant amount of storage space. For example, in a color printer which is capable of printing an image

with a resolution of 600 dots per inch (DPI) and where each color in the color space is represented by a 32-bit word, a frame buffer having a capacity of 128 megabytes is required to store all of the data which represents one page of information. The time required to render and store this much data is significant, and can appreciably slow down the overall printing process. Even in a multilevel monochrome device, in which each pixel might be represented with eight bits of information, the rendering time is still a significant part of the total printing process.

To reduce the amount of memory that is required, high resolution printers often compress the image data. However, the compression and decompression of the data are additional steps that can slow down the overall printing process. For this reason, it is desirable to optimize the rendering process wherever possible, to improve the speed with which printing can take place and/or reduce the memory requirements of a printer.

In the past, it has been possible to configure multilevel output devices to act as bi-level devices. In such a mode of operation, only a single bit per pixel is stored in the frame buffer. A smaller and simpler frame buffer can be used, and rendering time decreases proportionately to the pixel depth. This approach has two significant disadvantages, however. First, it requires explicit intervention by the user. Secondly, when configured as a bi-level device, it is impossible for the device to display intermediate shades of gray or color directly. Rather, a method such as halftoning must be employed.

Summary

To address the foregoing limitations associated with prior art systems, the present invention provides methods in accordance with independent claims 1, 8 and 11, and a system in accordance with independent claim 13. Further advantageous features, aspects and details of the invention are set forth in the dependent claims, the following description and the drawings. The claims are to be understood as a first non-limiting approach of defining the invention in general terms.

In accordance with one aspect of the present invention, the advantages of bi-level operation are achieved without requiring an image output device to be explicitly configured to operate as a bi-level device. An image to be generated on a printer or a display monitor is analyzed to determine whether it is made up of at most two colors, or two levels of a single color. If so, an indication is provided to a rendering device that a simpler rendering procedure, suitable for bi-level data, can be employed. However, complete data

relating the color and/or pixel depth of the image is retained. If the rendering device is capable of processing the image data in a bi-level format, it does so, to thereby reduce the rendering time and the amount of memory capacity that is required. If, however, the rendering device is not capable of operating in a bi-level mode, or conditions relating to the printing of a page make such a mode undesirable, rendering is carried out in a conventional fashion, i.e., in a full-color and/or multi-level mode. With this approach, the advantages of bi-level image processing are utilized. In addition, because of the reduced memory requirements, compression and decompression may not be necessary.

However, the flexibility to process an image in a conventional manner is maintained, thereby making the invention suitable for application in a variety of different types of image output devices.

Brief Description of the Drawings

Further features of the invention, as well as the advantages attained thereby, are explained in detail hereinafter with reference to a specific embodiment illustrated in the accompanying drawings.

Figure 1 is a block diagram of the main subsystems which make up a color printer of the type in which the present invention can be employed;

Figure 2 is a schematic representation of a full-color rendering process;

Figure 3 is a more detailed block diagram of the rendering device;

Figure 4 illustrates an example of a page of an image which is divided into horizontal bands;

Figure 5 is a flowchart of a first embodiment of the process of the present invention; and

Figure 6 is a flowchart of a second embodiment of the process of the present invention.

Detailed Description

To facilitate an understanding of the present invention, it is described hereinafter in the context of a specific embodiment. In particular, reference is made to the implementation of the invention in a color printer which employs a CMY color space to represent colors. It will be appreciated, however, that the practical applications of the invention are not limited to this particular embodiment. Rather, the invention can be employed in other types of image output devices, such as CRT monitors and LCD display screens, which employ any of a variety of multi-level color spaces, including monochrome devices which employ a single-component color space. In this regard, it is to be noted

that the reference to two colors in the following description does not necessarily mean two different colors. Rather, it also denotes two different levels of the same color, e.g. two different shades of gray.

Figure 1 is a block diagram of the major components of a color printer, of a type in which the present invention can be implemented. Referring thereto, the printer 10 includes an I/O controller 12 that is connected to one or more I/O ports for communication with computers and other external sources of data to be printed. A spooler 14 accumulates image data received from the external sources, and stores the data until it is ready to be processed for printing. It will be appreciated, of course, that the spooler is optional and can be incorporated in an external device, rather than the printer itself. An interpreter 16 receives a stream of image data and issues calls which cause the desired image to be drawn, or printed, on the paper. These calls can be of two basic types. One set of calls identifies the appearance state of objects to be drawn. This appearance state indicates the color of the object, as well as other appearance-related factors, such as patterns or the like. The other set of calls describes the object to be drawn, such as a rectangle, a line, a particular character of text, or the like. In the illustrated embodiment of the printer, these calls are stored in an intermediate form, known as a display list 18, or a metafile.

The information on the display list is provided to a renderer 20. The renderer converts the object-based information from the interpreter 16 into individual pixel display values, which are stored in a frame buffer 22. The pixel display values stored in the frame buffer can undergo optional processing within one or more processors 24. For example, the display values can be compressed and/or decompressed, or undergo halftone processing. Ultimately, these display values are supplied to a print engine 26, to control the actual printing of the desired image. The print engine could be of the laser beam printer type or the ink jet type, for example.

In an alternative embodiment of a printer, the display list 18 can be eliminated. In this embodiment, object information from the interpreter 16 is directly fed to the renderer 20, to be dynamically rendered as it is received.

The basic process which is undertaken in the renderer 20 is illustrated in greater detail in Figure 2 for a printer which represents colors by means of a three-component color space comprised of cyan, magenta and yellow. An exemplary document 28 to be printed on the printer contains four objects. For the sake of simplicity, these objects are represented as solid rectangles. In practice, the objects can be any geometric shape, lines, or characters of text. In

this particular example, each object has a different color, as represented by the different shading. The rectangle 30 is cyan, the rectangle 32 is magenta, the rectangle 34 is yellow, and the rectangle 36 is black.

5 The frame buffer 22 is comprised of three sections, 22C, 22M and 22Y, which respectively correspond to the three color components of the printer's color space. In the illustrated example, these sections are depicted as separate planes, in which each plane comprises a pixel map, having a storage location for each pixel in the image to be generated, as represented by the grid marks along the edges of each plane. In practice, the information pertaining to the
10 respective color components can be stored in the frame buffer in any desired manner. For example, the three color component values for a given pixel can be stored together as three contiguous bytes in the memory.

In operation, the interpreter 16 issues a call to set the state of the printer to print the color cyan, and then issues a call to draw the rectangle 30. In
15 response to the calls to draw the cyan rectangle 30, the renderer 20 stores information in the frame buffer section 22C which describes each pixel in the image that is to contain the color cyan. This stored information includes the saturation value, or intensity, for the displayed color at the respective pixel.

The renderer 20 operates in a similar manner for the calls pertaining to
20 the drawing of the magenta rectangle 32 and the yellow rectangle 34. In particular, information pertaining to the saturation value of the magenta rectangle 32 is stored at appropriate address locations in the magenta section 22M of the frame buffer, and saturation values for the yellow rectangle 34 are stored in the yellow section 22Y of the frame buffer.

25 In a device which employs a CMY color space, the color black is represented by 100% saturation of each of the cyan, magenta and yellow components. Therefore, in response to the calls to draw the black rectangle 36, the renderer 20 stores the appropriate saturation information for the same pixel in each of the three frame buffer sections 22C, 22M and 22Y.

30 Once all of the information for the page of data is stored in the frame buffer 22, it is provided to the print engine 26, with any optional intermediate processing. More particularly, the information from each of the three sections 22C, 22M and 22Y of the frame buffer is individually provided to the print engine in three separate steps. For example, all of the cyan information may be
35 printed, followed by all of the magenta information and then all of the yellow information, to form a composite image.

In a monochrome printer, all of the image data is rendered into a single plane. In this case, the colors cyan, magenta and yellow for the objects 30, 32

and 34 are represented as different grayscale levels. The information stored in the frame buffer 22 indicates the respective grayscale level for the pixels covered by each object.

It can be appreciated that the time required to render objects in an image consumes a significant portion of the overall processing that is required to generate the image. For example, in a three-color output device having a pixel depth of eight bits, twenty-four bits must be calculated and stored for each pixel in the image. Furthermore, a significant amount of memory is required to store all of the information in the frame buffer that is necessary to produce a high quality, high resolution image, particularly for color images. To the extent that the rendering time and/or memory requirements can be reduced, the overall process for generating an image can be made more efficient.

Storing image data in an intermediate form, such as the display list 18, provides an opportunity to analyze and preprocess image data in a manner which permits the rendering process to be optimized. To provide a more complete understanding of this concept, the manner in which image data is handled by the interpreter and the renderer is described in greater detail with reference to Figure 3. Referring thereto, the interpreter 16 issues calls to draw objects. In the illustrated embodiment, these calls are captured by the renderer 20. The renderer is comprised of two major portions, a capture component 40 and a playback component 42. The capture component 40 intercepts the calls from the interpreter 16, and stores them in the display list 18. The playback component 42 retrieves the image data from the display list 18, and performs the rendering process to generate the pixel data, which is stored in the frame buffer 22. This pixel data is uncompressed, i.e., at the full bit depth of the printer.

In a preferred implementation of the invention, an image is divided into one or more non-overlapping areas, and processed area-by-area. For example, a page can be divided into horizontal bands 28a-28e, as shown in Figure 4. In the illustrated example, the page is divided into five such bands. In actual practice, the page can be divided into any number of bands. In this regard, the non-overlapping areas need not be horizontal bands. They can have any shape which enables the entire page to be covered. The image data that is stored in the display list is sorted by band.

Referring again to Figure 3, the playback device 42 retrieves the image data for one band of the page, e.g. descriptions of objects, and renders it to generate the pixel data in the frame buffer 22. This process is repeated for each band, until the frame buffer contains the data for a complete page of the image.

If desired, the data for each band can be compressed before it is stored in the frame buffer. The data in the frame buffer 22 is provided to an engine manager 46 at the time the image is to be printed. The engine manager 46 decompresses the data in the frame buffer at print time, if necessary, and provides a video
5 signal to drive the print engine. A controller 48 communicates with the renderer 20 and the engine manager 46 to control the printing operation. The controller functions as a memory manager, and allocates memory for the frame buffer in accordance with the requirements and capabilities of the engine manager, as discussed in detail below.

10 In one implementation of the present invention, the image data received from the interpreter 16 is analyzed in the capture component 40 to determine whether a relevant segment, such as a page or a band, is comprised solely of bi-level color information. A common example of a bi-level image is a page of text. When the interpreter 16 issues calls to print such a page, all of
15 the appearance state calls contain instructions to print the color black. As such, the entire page consists of only two colors, namely black objects, i.e. text, and a white (or other non-black) background. Although a black and white page of text is the most common example, the invention is applicable to any other type of two-color image, such as an arrangement of yellow objects on a blue
20 background, or an image consisting of two different shades of gray.

In one implementation of the present invention, the appearance state calls from the interpreter are examined to determine whether a maximum of two colors are called for. If so, an indication of this fact is stored in the display list 18, along with the calls from the interpreter 16. During playback, the
25 renderer 20 provides an indication to the controller 48 that the image data about to be rendered contains only bi-level color information. In response to the information from the playback device 42 that bi-level color is present, the controller determines whether the engine manager 46 is capable of operating in a bi-level mode, and whether printing conditions are otherwise suitable for
30 use of the bilevel mode. More particularly, an engine manager which is capable of operating in a bi-level mode can receive a single bit which indicates a black or white pixel, for example, and expand it into the appropriate number of bits to drive the engine. Thus, if the printer is capable of generating 16 levels of gray, in the bi-level mode the engine manager expands each bit of data from
35 the frame buffer into a 4-bit signal.

For example, if an image is made up of black characters on a white background, in the bi-level mode the color black might be stored in the frame buffer as a logical one bit, and white pixels might be represented as a logical

zero. At print time the engine manager 46 can expand each bit into a corresponding 4-bit signal, e.g. 1111 for black and 0000 for white in the case of a monochrome printer. If, instead, the image is comprised of 50% gray objects on a white background, each logical one bit is expanded to a 50% gray value, e.g., 0111. As another example, in a bi-level color image, a logical one bit might represent blue and a logical zero bit might represent yellow. In this case, the engine manager expands each logical one bit to a 12-bit value for blue, e.g. 1111 1111 0000 (corresponding to 100% cyan, 100% magenta and 0% yellow), and each logical zero bit is expanded to a 12-bit value for yellow, e.g., 0000 0000 1111.

If the engine manager 46 can operate in such a mode, only one bit of data is needed to indicate the display value for each pixel of the image. As such, the rendering time can be significantly reduced, to thereby increase performance. In addition, a much smaller amount of total memory is required. In such a case, therefore, the controller 48 allocates less memory for the frame buffer 22.

Furthermore, the need to compress the data may be eliminated. For example, a page of uncompressed image data having a resolution of 600 dots per inch may require only about 4 megabytes of total memory capacity for the entire frame buffer when the bi-level mode is employed. If the printer has that much memory available, there is no need to compress the pixel data.

However, if the engine manager is not capable of operating in a bi-level mode, all of the information necessary to operate in a normal, full pixel depth mode is available in the display list 18. In this case, the controller 48 allocates sufficient memory to the frame buffer 22 to store the required number of bits per pixel, e.g., twenty-four or thirty-two bits per pixel in a full color printer.

The operation of the capture device 40 to determine whether the incoming image data is bi-level in nature is depicted in the flow chart of Figure 5. Preferably, the determination is made on a band-by-band basis. After each band is examined and a determination is made, the determinations for all of the bands can be summed to make a final determination for the entire page.

Referring to Figure 5, as each drawing call is received (Step 49) from the interpreter 16, it is examined at Step 50 to determine whether it is a state call, i.e. one that sets the color of the printer. If not, the call is stored in the display list at Step 52 for its band.

If the call from the interpreter is a state call, a check is made at Step 54 whether this is the first state call for the page. If so, the color required by the call, e.g. black, is stored in a buffer at Step 56, and a set of flags for the respective bands are each set to a true state at Step 58. The call is then stored on the display list, at Step 52.

If the retrieved state call is not the first call for the page, a determination is made at Step 60 as to which band, or bands, are affected by the call. Referring to Figure 4, a call pertaining to the rectangle 30 affects only one band 28b, whereas calls relating to the rectangle 32 cover three bands, 28b, 28c and 28d.

5 The band flag BFLAGi for the first affected band is checked at Step 62 to determine whether it is still in the true state. If not, a determination has already been made that the band does not consist solely of bi-level color data, and the call is stored on the display list for the current band at Step 52. If the flag is in the true state, however, at Step 64 the color that is being called for is
10 compared with the color previously stored in the buffer at Step 56. If they are the same color, the call is merely stored on the display list. If, however, the colors are not the same, the band flag BFLAGi is set to the false state at Step 66 to indicate that the color data for that band is not bi-level, and the call is then stored on the display list. At Step 53 a determination is made as to whether or
15 not there are additional bands, and if so, this procedure is repeated for each band that is covered by the state call. Every call is examined in this manner, until the end of the page is reached (Step 55), i.e. a call to eject the page is received.

At rendering time, the band flags are checked to determine whether the
20 image data is bi-level. Depending upon the capabilities of the engine manager, it may be desirable to operate in the bi-level mode on a band basis or on a page basis. If operation is carried out on a page basis, all of the band flags are checked, to see if they are in the true state. If so, an indication is provided to the controller 48 that the color data is bi-level. In response, the controller
25 allocates memory for a bi-level frame and bi-level rendering takes place. Otherwise, no further action is taken and the rendering process proceeds in the normal, full-bit fashion.

In the foregoing example, only one color is stored at Step 56. In such a case, the second color is that of the paper on which the image is printed, e.g.,
30 white. As an alternative, the first two state calls can be stored at Step 56, to store both colors which will comprise the image.

In a preferred embodiment of the invention, when the color data is determined to be achromatic as well as bi-level, it is rendered in the manner disclosed in co-pending United States Patent Application Serial No. 08/483,453
35 entitled " Method and System for Rendering Achromatic Image Data for Image Output Devices" filed June 6, 1995. More particularly, when the color to be printed or displayed is black or another grayscale value, it is not rendered into all three sections of the frame buffer, as shown in Figure 2. Rather, as disclosed

in the related application, the color data is only rendered into one section of the frame buffer, and the rendered data is read from that section for the printing or display of all three colors. In such a case, the printing process is further optimized, through additional reduction of the rendering time.

5 In the example of Figure 5, all of the data is examined as it is stored in the display list, and a determination can be made prior to rendering whether the bi-level mode of operation is possible. The process of the present invention is also applicable to output devices which do not utilize a display list, in which case the interpreted calls are sent directly to the renderer. In this
10 case, the bi-level determination is carried out dynamically.

Referring to Figure 6, in the dynamic mode of operation state calls are examined, as in the process of Figure 5, and flags are set to indicate whether the color data is bi-level. As each object is rendered the state of the bi-level flag for each band covered by the object is checked at Step 70. If it is false, the object is
15 rendered in the normal, multi-level mode at Step 72. On the other hand, if the flag is true, the object is rendered in a bi-level mode at Step 74, where each pixel is assigned a value of either one or zero.

Whenever a state call requests a change in color, it is checked at Step 76 to determine whether the new color is one of the two previously selected
20 colors. If not, bi-level operation is no longer possible. In this case, a full-bit-depth frame buffer is allocated in memory, and the previously rendered bi-level values are expanded to the full bit depth at Step 78. The flag for the affected bands are set to the false state at Step 80, and from that point on all rendering for the affected bands takes place in the normal, multi-level mode of
25 operation.

From the foregoing, it can be seen that the present invention examines image data prior to or as it is being rendered, in a manner which increases the overall efficiency of the rendering process. By recognizing those situations in which the image is comprised of a maximum of two colors, a bi-level mode of
30 operation can be employed to significantly reduce rendering time, as well as storage requirements for the frame buffer. In such a situation, compression of the image data may not be required, to further increase the speed with which the image generation can be completed. Furthermore, by streamlining the rendering process commensurate with achromatic image data, additional
35 optimization of the process can be attained.

It will be appreciated by those of ordinary skill in the art that the present invention can be embodied in other specific forms without departing from the spirit or essential characteristics thereof. For example, although disclosed with

specific reference to its implementation in a printer using CMY color space, the invention is equally applicable to other types of color output devices and other single- or multi-dimensional color spaces. The presently disclosed embodiments are therefore considered in all respects to be illustrative, and not
5 restrictive. The scope of the invention is indicated by the appended claims, rather than the foregoing description, and all changes that come within the meaning and range of equivalence thereof are intended to be embraced therein.

What Is Claimed Is:

1. A method for generating an image in an image output device that represents color by means of a multi-level color space, said method comprising
5 the steps of:
 - receiving image data which defines objects that form an image to be generated;
 - examining said image data to determine whether it represents a maximum of two colors in an image to be generated;
 - 10 rendering the image data in a bi-level mode, where each pixel in the image is assigned a data value that is in one of two states and the pixel data values are stored in a memory, when a maximum of two colors are represented;
 - expanding the stored pixel values into multi-level pixel values;
 - 15 and
 - generating an image using said multi-level pixel values.
2. The method of claim 1, further comprising the step of storing said image data in an intermediate form prior to said rendering step, wherein said
20 examining step is carried out as the data is being stored in said intermediate form.
3. The method of claim 2, further comprising the step of storing an indicator with the data in said intermediate form which indicates whether a
25 maximum of two colors are represented.
4. The method of one of claims 1 to 3, wherein said expanding step is carried out after all of the data for the image has been rendered.
- 30 5. The method of one of claims 1 to 3, wherein said examining step is carried out as the image data is being rendered.
6. The method of one of claims 1 to 5, further comprising the steps of:
35
 - detecting that more than two colors are represented in said image data as it is being rendered; and
 - carrying out said expanding step before all of the data for the image has been rendered.

7. The method of claim 6, further comprising the step of rendering the image data in a multi-level mode after said detecting step, where each pixel is assigned one of multiple states that are greater than two in number.

5

8. A method for generating an image in an image output device that represents color by means of a multi-level color space, said method comprising the steps of:

10 receiving image data which defines objects that form an image to be generated;

storing the received image data in an intermediate form;

inspecting said image data to determine whether it represents a maximum of two colors in the image to be generated;

15 storing an indication of bi-level color data with the stored image data when the received image data represents a maximum of two colors in the image; and

retrieving the stored image data and generating a bi-level color map when said indication is stored with the image data.

20 9. The method of claim 8 wherein said bi-level color map comprises a single-bit display value for each of said picture elements.

10. The method of claim 8 or 9, further comprising the step of expanding said display values into multi-bit values that correspond to
25 components of said color space, and generating an image from said multi-bit values.

11. A method for generating an image in an image output device that represents color by means of a multi-level color space, said method comprising
30 the steps of:

receiving image data which defines objects that form an image to be generated;

35 rendering the image data in a bi-level mode, where each pixel in the image is assigned a data value that is in one of two states, and storing the pixel data values in a memory;

examining said image data while it is being rendered to determine whether it represents a maximum of two colors in an image to be generated;

detecting that more than two colors are represented in said image data;

expanding the stored pixel values into multi-level pixel values in response to said detection; and

5 generating an image using said multi-level pixel values.

12. The method of claim 11, further comprising the step of rendering additional image data in a multi-level mode after said detecting step, where each pixel is assigned one of multiple states that are greater than two in
10 number.

13. An image producing system of the type in which color is represented in a multi-component color space, comprising:
an interpreter for generating commands to produce images of
15 objects;
an inspector which inspects said commands to determine whether the images of the objects are comprised of bi-level color;
a renderer responsive to said commands for storing a pixel map which defines an image of an object for at least one component of said color
20 space;
an image generating unit for generating an image in accordance with information contained in said pixel map; and
a controller responsive to said inspecting means for causing said
renderer to generate a bi-level pixel map when the image of the data is bi-level
25 in color.

14. The image producing system of claim 13, further comprising means for expanding bi-level data values stored in said pixel map into multi-level values for presentation to said image generating unit.
30

15. The image producing system of claim 13 or 14, wherein said controller allocates memory for use by said renderer to store said pixel map, and wherein the amount of memory that is allocated to said renderer is dependent upon whether the images of the objects are comprised of bi-level
35 color, as determined by said inspecting means.

1/4




FIG. 1




FIG. 2

2/4




FIG. 3




FIG. 4

3/4




FIG. 5

4/4




FIG. 6

INTERNATIONAL SEARCH REPORT

Int. Application No
PCT/US 96/07301

A. CLASSIFICATION OF SUBJECT MATTER
IPC 6 G06T11/00

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 6 G06T

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	PATENT ABSTRACTS OF JAPAN vol. 018, no. 065 (M-1554), 3 February 1994 & JP 05 286170 A (MATSUSHITA ELECTRIC IND CO LTD), 2 November 1993, see abstract	1,6,8, 11,13
A	--- EP 0 395 032 A (KONISHIROKU PHOTO IND) 31 October 1990 see page 3, line 51 - page 4, line 36 see page 5, line 52 - line 56	1
P,A	--- EP 0 660 583 A (CANON KK) 28 June 1995 see column 3, line 44 - line 46; claim 1	1
A	--- US 5 383 037 A (KIMURA SHUNICHI ET AL) 17 January 1995 see column 5, line 11 - column 6, line 2 -----	1

☐ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents :

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the international filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

- *T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- *X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- *Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- *&* document member of the same patent family

Date of the actual completion of the international search

5 September 1996

Date of mailing of the international search report

23.09.96

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax (+31-70) 340-3016

Authorized officer

Perez Molina, E

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/US 96/07301

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
EP-A-0395032	31-10-90	JP-A- 2288670 US-A- 5109274	28-11-90 28-04-92
EP-A-0660583	28-06-95	JP-A- 7177363 JP-A- 7203164 EP-A- 0660581 EP-A- 0660582	14-07-95 04-08-95 28-06-95 28-06-95
US-A-5383037	17-01-95	JP-A- 5130427	25-05-93

THIS PAGE BLANK (USPTO)